



Description

The NC-220 ZF3 3 input transmitter can be used anywhere a N/O contact is required. A fully standalone wireless device that can be placed anywhere in a facility, the NC-220 has powerful user serviceable CR123A battery for long battery life.

Enclosed in a compact PVC box the NC-220 ZF3 has 3 terminal block input and an internal button for configuration. Each input is uniquely identified and input 1 can be configured as a cancel at source. A great solution for door contacts, motion sensors and auxiliary smoke detectors.

Install with the included 4 mounting screws or hide in the ceiling area for a clean look to your hardwired devices.

Features

- 3 screw down inputs
- LED indicator
- Long battery life with a standard CR123A battery
- Batteries are easily changed by maintenance staff
- Low battery indicator which routes to special reports for maintenance staff and their own electronic checklist of completed maintenance
- Can be placed anywhere in the facility
- Fully supervised heartbeats to Central ensuring 24/7 operation

Technical Specifications

Standards:	UL 1069, 2560, CSA 22.2 #205, FCC Part 15, Class "B", CS-03
Power Options:	Input Power: <ul style="list-style-type: none"> • 1 x 3V CR123A Battery • Nominal Current 35mA
Wireless Characteristics:	Frequency: 2.4Ghz Network type: 802.15.4 wireless mesh network Range: 75ft
Physical Characteristics:	Enclosure: Plastic Color: Black Weight: 1.6oz (45g) Dimensions of Enclosure: 3.3"H x 2.2"W x 1.5"D Operating Temperature: 0° C to +50° C
Input Operating Specifications:	Wet contact pair, supplied voltage is max 3.6V Nominal current of 1.4mA (external loop closed) and an absolute maximum of 5mA. Follow manufacturer's specifications for any attached equipment or wiring.

Ordering Information

Model	Description
NC-220	ZF3

NOT TO BE USED FOR INSTALLATION PURPOSES.



Canada
 25 Interchange Way
 Vaughan, Ontario L4K 5W3
 Telephone: (905) 660-4655
 Fax: (905) 660-4113

U.S.A.
 4575 Witmer Industrial Estates
 Niagara Falls, NY 14305
 Toll Free: (888) 660-4655
 Fax Toll Free: (888) 660-4113

Distributed by:

Web page: <http://www.mircomgroup.com> Email: mail@mircomgroup.com

ISO 9001:2008
 REGISTERED



CAT. 9203
 Rev. 1